

Blasting guns

- Pneumatically powered -

A pneumatic motor rotates the barrel and the attached blasting tools (multiple nozzle heads)

Type SP 2500 PR 1 MB

Mechanical Bypass



Op. pressure: 36300 psig
Flow rate: 5.3 gpm
Rotation speed: 1000-3000 r.p.m.
Barrel length: 11.8 – 29.5 inch

Type SP 3000 PR 1 und PR 2

Electrical Bypass



Op. pressure: 43500 psig
Flow rate: 5.3 gpm
Rotation speed: 1000-3000 min.⁻¹
PR 2 10-600 min.⁻¹
Barrel length: 11.8 – 29.5 inch

Type SP 3000 PR 3 ER

Electrical Bypass for tube cleaning



Op. pressure: 43500 psig
Flow rate: 5.3 gpm
Rotation speed: 10-600 min.⁻¹
Barrel length: 11.8 inch

Type SP 3000 PR 1 / 1D

Electrical Bypass by 1 wire technology



Op. pressure: 43500 psig
Flow rate: 5.3 gpm
Rotation speed: 1000-3000 min.⁻¹
Barrel length: 11.8 – 29.5 inch

Bypass guns

- Pneumatically powered -

Type SP 3000 PR 3 R

Tube cleaning (bypass controlled by separate electrical switch)



Op. pressure: 43500 psig

Flow rate: 5.3 gpm

Rotation speed: 10-600 min.⁻¹

Barrel length: 11.8 inch

Type SP 3000 PR 3 / 1D

Tube cleaning / Electrical bypass by 1 wire technology



Op. pressure: 43500 psig

Flow rate: 5.3 gpm

Rotation speed: 10-600 min.⁻¹

Barrel length: 11.8 inch

Type SP 3000 PR1 / 1D / 2HD

For two hand operation / Electrical bypass by 1 wire technology



Op. pressure: 43500 psig

Flow rate: 2.6 gpm

Rotation speed: 1000 - 3000 min.⁻¹

Barrel length: 8.9 inch

6/07 © Copyright Hammelmann Maschinenfabrik GmbH, Oelde, Germany. Subject to modification.

Hammelmann Corp. 600 Progress Road
Dayton, Ohio 45449
eMail: mail@hammelmann.com

Phone (001) 937-859-877
Fax (001) 937-859-9188
<http://www.hammelmann.de>

HAMMELMANN®