

# RD Flex 3

## Rotorjets with adjustable rotation speed

It is not necessary to fit differing size nozzle inserts to the RD Flex 3000 to achieve the various speeds or to suit various pump performances. Nozzle insert selection is therefore simpler and safer.



Nozzle carriers can be exchanged very easily to suit the type of work in hand or the power of the pump being used.



The rotation speed is simply adjusted by turning the adjuster ring in the required direction.

Despite the additional features the Rotorjet is still extremely lightweight.

The optimal nozzle positions for the various types were selected as a result of CFD analysis.

4000 r.p.m.



High speed for coating removal.

1000 r.p.m.



Low speed for concrete removal or surface roughening.

# RD Flex 3000

## Technical Data

Op. pressure: max. 43500 psig  
 Flow rate: 2.2 – 7.9 m<sup>3</sup>/h  
 Rotation speed: 1000-4000 rpm

Material: corrosion resistant  
 Weight: 3.9 lbs including nozzle carrier and nozzle inserts  
 Length: 9.29 inch  
 Diameter: 2.91 inch  
 Connection thread: M 14 x 1,5 LH,  
 Optional: Adapter for 9/16"–18 UNF  
 Spanner size: 0.94 inch A/F  
 Number of inserts: max. 6

Suitable inserts:

Type K  
Round jet



Material:  
Steel/Sapphire  
(only for RD  
Flex 3004)

Type P  
Round jet



Material:  
Steel/Sapphire

Type T  
Round jet



Material:  
Steel/Diamond








## RD Flex 3000

- Designed for use with the SP 3000 and Ergoblast guns, lances etc.
- Low wear, leakage free rotating components
- Internal protected brake
- Quick change seal system
- Nozzle inserts are countersunk in the nozzle carrier.
- Nozzle carrier protected by blastback shield
- Plastic protective sleeve

## Typical applications

- Renovation: surface layer (render etc.) removal, Paint removal, Facade cleaning
- Cleaning and washing concrete structures
- Expansion joint removal
- Side wall cleaning in phosphate plants
- Coating and paint removal from metal surfaces
- Blasting pipe externals
- Paint booth grid and skid clean up
- Hull, deck and superstructure surface preparation, Heavy machinery clean up in the ship repair industry

Type	Pump power	Code no.
 RD Flex 3001	74 – 94 HP	00.00786.0079
 RD Flex 3002	94 – 160 HP	00.00786.0080
 RD Flex 3003	94 – 160 HP	00.00786.0083
 RD Flex 3004	94 – 160 HP	00.00786.0089
 RD Flex 3005	94 – 160 HP	00.00786.0090

- Corrosion and paint removal in holds, ballast tanks, double hull spaces etc.
- Surface preparation on awkward metal profiles
- Bridge structural steelwork surface preparation
- Rubber coating removal



**When working with hand held guns or lances the maximum allowable axial reaction force is 250 N. If the reaction force exceeds 150 N the blasting tool must be fitted with a support device such as a shoulder stock.**

Hammelmann Corp.

600 Progress Road  
 Dayton, Ohio 45449  
 eMail: mail@hammelmann.com

Phone (001) 937-859-8777  
 Fax: (001) 937-859-9188  
 http://www.hammelmann.com

