

Blasting guns

- with electrical control signal -

The electrical control signal switches the pump bypass control to open (no pressure) or close (pressure on) the bypass valve.

Type SP 400 ME
Mechanical/Electrical




Op. pressure: 400 bar
Flow rate: 33 l/min
Barrel length: 500 – 1000 mm

Type SP 1000 ME
Mechanical/Electrical




Op. pressure: 1000 bar
Flow rate: 33 l/min
Barrel length: 250 – 4000 mm

Type SP 1000 EB
Electrical Bypass



Op. pressure: 1000 bar
Flow rate: 33 l/min
Barrel length: 250 – 4000 mm

Type SP 1500 E
Electrical



Op. pressure: 1500 bar
Flow rate: 33 l/min
Barrel length: 300 – 2500 mm

Blasting guns

- with electrical control signal -

Type SP 2500 MBE
Mechanical/Electrical Bypass



Op. pressure: 2500 bar
Flow rate: 30 l/min
Barrel length: 300 – 2500 mm

Type SP 3000 – 2H
Electrical two hand operation



Op. pressure: 3000 bar
Flow rate: 30 l/min
Barrel length: 300 – 2500 mm

Type SP 3000 E
Electrical



Op. pressure: 3000 bar
Flow rate: 30 l/min
Barrel length: 300 - 2500 mm

Type SP 3000 E 1D
Electrical with 1 wire technology



Op. pressure: 3000 bar
Flow rate: 30 l/min
Barrel length: 300 – 2500 mm

Type SP 3500 E 1D
Electrical with 1 wire technology



Op. pressure: 3500 bar
Flow rate: 30 l/min
Barrel length: 300 – 2500 mm

07/07 © Copyright Hammelmann Maschinenfabrik GmbH, Oelde, Germany. Subject to modification.

Hammelmann
Maschinenfabrik GmbH

Postfach 3309 • D-59282 Oelde
Zum Sundern 13-21 • Germany
eMail: mail@hammelmann.de

Telefon (0 25 22) 76-0
Telefax (0 25 22) 76-444
Internet: www.hammelmann.de

HAMMELMANN[®]