

Multiple nozzle heads for SP 2500 PR / SP 3000 PR

Max. op. pressure: 2500 bar / 3000 bar
 Connection thread: M 14 x 1,5 LH
 with internal conical seal

DH 1



Nozzle inserts		Applications
Material	Weight	
2 x Inserts M 10 "Type P" max. 3000 bar		Concrete reconditioning: Roughening, Removal Weld seam preparation: Slag removal
Stainless	0,5 kg	

DH 2



2 x Inserts M 10 "Type P" max. 3000 bar		Concrete reconditioning: Exposing reinforcing bars
Stainless	0,4 kg	

DH 5



6 x Inserts M 10 "Type P" max. 3000 bar		Surface preparation: Stripping paint from metals. Use with protective cover if removing abrasive non skids
Stainless	0,8 kg	

DH 6



5 x Inserts M 10 "Type P" max. 3000 bar		Surface preparation; Stripping paint from metals
Stainless	0,7 kg	

Multiple nozzle heads for SP 2500 PR / SP 3000 PR

Max. op. pressure: 2500 bar / 3000 bar
 Connection thread: M 14 x 1,5 LH
 With internal conical seal

DH 7



Nozzle inserts		Applications
Material	Weight	
8 x Inserts M 10 "Type P" max. 3000 bar		Surface preparation; Stripping paint from metals; Wide stripping width
Stainless	1,4 kg	

DH 8



6 x Inserts M 10 "Type P" max. 3000 bar		Profile surface preparation; Stripping paint from metals – H beams. – Angled stiffeners etc.
Stainless	0,6 kg	

DH 09



6 x Inserts M 6 x 0,75 "Type "O" max. 3000 bar		Profile surface preparation; Stripping paint from metals - H beams. – Angled stiffeners etc.
Stainless	0,15 kg	

DH 10



7 x Inserts M 4 + adhesive "Type N" max. 2500 bar		Hardened nozzle head for stripping very small structural members - H beams. – Angled stiffeners etc.can be adapted for tube cleaning
Stainless	0,1 kg	